

Bluetooth Ver2.0+EDR USB

Bluetooth Ver2.0+EDR2.0 USB dongle

BT-MicroEDR2
JAN Code : 4941250163434



Estimated Range
10m
Class 2



The PCI Mini USB Bluetooth adapter[BT-Micro EDR2] is endorsed with CSR V2.0 EDR chipset which has 3 times faster transmitting rate than standard Bluetooth technology. As Bluetooth becomes popular in wireless communication, the latest introduction of PCI Bluetooth 2.0 is certainly the best choice to exploit Bluetooth application.

Support Bluetooth Profiles

A2DP	Advanced Audio Distribution Profile	HSP	Headset Profile
AVRCP	Audio/Video Remote Control Profile	HID	Human Interface Device Profile
BIP	Basic Imaging Profile	LAP	LAN Access Profile
DUN	Dial-up Networking Profile	OPP	Object Push Profile
FAX	Fax Profile	PAN	Personal Area Networking Profile
FTP	File Transfer Profile	SPP	Serial Port Profile
GAVDP	General Audio/Video Distribution Profile	SYNC	Synchronization Profile
HCRP	Hard Copy Cable Replacement Profile		

BT-MicroEDR2 Specifications

Standard	Bluetooth EDR 2.0, Class II
Interface	USB2.0 (TypeA)
Antenna	Chip on-board
Frequency Range	2.4GHz~2.4835GHz ISM Band
Driver	Toshiba / IVT
Power Consumption	70mA (working time)
Data Speed	Up to 2.1Mbps
Receiver Sensitivity	-80dBm @0.1%BER
Operating Range	10m
Operating Temperature	-10 ~ 55 °C
Storage Temperature	-20 ~ 65 °C
Operating Humidity	10 to 90% (non-condensing)
DC Power(Supply voltage)	5V from USB
Dimension	19(L)*14.34(W)*4.5(H)mm
Weight	5.5g
EMI	CE,FCC,NCC,TELEC

Package Contents

- BT-MicroEDR2
- QIG(Quick Installation Guide)
- CD-ROM(Driver&Utility)
- Warranty Card

New Arrival at the end of November, 2007