

EH-507 5Ports 10M Repeater Hub



▶ Feature

The EH-507 repeater HUB implements low-power consumption technology with fanless and noiseless architecture.

■ Built-In Magnets for Easy Installation

The magnets at the base of the unit allow easy installation on various locations, such as steel desks and cabinets.

■ Supplied with an AC Adapter

The EH-507 comes with an AC adapter as well as a short cord, which prevents interference with other plug outlets in the power tap.

■ Fanless and Noiseless Architecture

The fanless architecture of the EH-507 employs no cooling fans at all. The product creates a comfortable working environment with total noiseless.

■ Uplink Port

The EH-507 is equipped with an Uplink port for cascade connection with other hubs. The setting, available through a changing-over-switch, allows for the cascade connection via straight-through, not crossover cable.

▶ Specification

EH-507	
Standards Conformance	IEEE802.3 10BASE-T
Supported Media	UTP / STP Cable 10Mbps: Category 3 or Greater
Number of Ports	10BASE-T (RJ-45) x5 (including changing-over switch port x 1 to enable Uplink port)
Transfer speed	10Mbps
LED	Link / Act, Power, Col.
Power Consumption	1.6W Max
Operating Temperatures	0 ~ 45 degrees Celsius

Operating Humidities	35% ~ 80% (Non- Condensing)
Dimensions	126(W) x 29(H) x 68(D)mm
Weight	150g
Package Contents	EH507, AC Adapter, Short Cord, Magnets.

Product View

