



## 1Port 10M Print Server Mini2



### Feature

Since the product supports TCP/IP, IPX/SPX and NetBEUI protocols, it enables printer sharing in i)peer-to-peer networks based on Windows95/98/Me/2000, ii)Server/Client networks based on Windows NT and NetWare as well as iii)various UNIX based environments. Furthermore, it can be easily configured via the supplied configuration utility for Windows.

Support for AppleTalk, Web Management and SNMP has been added to the product since its 1999 October shipment.

- Skeleton Type(Blue)
- Complies with IEEE802.3 10BASE-T
- Provides one RJ-45 STP port for 10BASE-T connectivity
- Provides one Centronics parallel port that supports direct attachment to a printer
- Supports TCP/IP protocols and NetBEUI protocols
- LED indicators display the operating status of the print server in real time
- On-board Flash ROM enables firmware upgrade
- Supports Windows 95/98/Me, Windows 2000, WindowsXP, Windows NT, NetWare 3.X/4.X and UNIX OSes
- \* The print server does not support printers that either utilize or require bidirectional parallel port or WPS (Windows Printing System).
- \* The Mini can not be used with Macintosh computers.

#### ■ Option Parallel Cable

Model Number: **PS-CB discontinued**

(Use this cable when the product cannot be directly attached to the parallel connector of the printer, or when you wish to keep some distance between the printer and Mini2.)

#### ■ Key Features of the Mini Series Products

Model Number	Standard Conformance	Web Management	AppleTalk Support	SNMP Support
Mini100w	10/100Base	O	O	O
Mini100plus	10/100Base	O	O	O
Mini300plus	10/100Base	O	O	O
Mini300m	10/100Base	X	O	O
Mini300	10/100Base	O	O	O
Mini100	10/100Base	O	O	O
Mini100m	10/100Base	X	O	O
Mini2	10Base	O	O	O
Mini	10Base	X	X	X

**Specifications**

Model Number	Mini2
<b>Access Method</b>	CSMA/CD 10Mbps
<b>Supported Standards</b>	IEEE802.3 ,10BASE-T
<b>Data Transfer Speed</b>	10Mbps
<b>Supported Media</b>	UTP/STP Cables, Category 3 or greater
<b>Network Port</b>	10BASE-T RJ-45 Port x 1
<b>Parallel Port</b>	10BASE-T/100BASE-TX RJ-45 Port x 1
<b>LEDs</b>	Power/Tx ,Lk/Rx ,LPT
<b>Power Supply</b>	DC6V ,800mA
<b>Power Consumption</b>	3W Max
<b>Operating Temperatures</b>	0 - 40 degrees Celsius
<b>Operating Humidity</b>	35 - 85% (non-condensing)
<b>Dimensions</b>	90(W) x 30.5(H) x 65(D)mm
<b>Weight</b>	100g
<b>EMI</b>	FCC Class A ,CE

▼ Product view

